

GLUTICIDE 15

A microbiocide for controlling slime-forming bacteria, sulfate-reducing bacteria and algae in air washers and recirculating cooling water systems; service water and auxiliary systems; heat transfer systems.

GUARANTEE: Glutaraldehyde 15% By Weight

REGISTRATION NO: 31043 Pest Control Products Act

USES:

- AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS, RECIRCULATING COOLING AND PROCESS WATER SYSTEMS
- INTERMITTENT (SLUG DOSE) METHOD
- CONTINUOUS FEED SYSTEM
- PASTEURIZER COOLING WATER SYSTEM
- SERVICE WATER AND AUXILIARY SYSTEMS
- HEAT TRANSFER SYSTEMS (Evaporative Condensers, Hydrostatic Sterilizers and Retorts, and Pasteurizers and Warmers)

Initial Dose: when the system is noticeably fouled, add 333 mL - 1333 mL of Gluticide 15 per 1000 L of water in the system. Repeat until control is achieved.

Subsequent Dose: when microbial control is evident, add 100 mL – 333 mL of Gluticide 15 per 1000 L of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment begins.

FOR COMMERCIAL USE

